MONTANA STATE AVIATION SYSTEM PLAN 1995 UPDATE FIELD INSPECTION FORM

AIRPORT:	DILLON (DLN)	AIRPORT REFERENCE CODE: B-II (SM)
CITY:	DILLON	APPROACH TYPE: NPI
CONTACT:	CECIL JONES	DATE INVENTORIED: 12-24-95
PHONE #:	683-6151	INSPECTED BY: RSD

	REQUIRED	ACTUAL	ALP	CONFORM
RUNWAY 16/34 INVENTORY				
DISTANCE TO:				
HOLD LINES FROM CENTERLINE:	125'	150'		✓
PARALLEL TAXIWAY FROM CENTERLINE:	240'	240'		✓
AIRCRAFT PARKING FROM CENTERLINE:	250'	275'		/
RUNWAY WIDTH:	75'	75'		/
RUNWAY LENGTH:	6,430'		6,500'	/
RUNWAY SAFETY AREA (RSA) WIDTH:	150'	OK	,,,,,,,	1
RUNWAY OBJECT FREE AREA (OFA) WIDTH:	500'	(1) - (5)		NO
PRIMARY / TRANSITION SURFACE PENETRATIONS:	500' W & 7:1	(2) - (6)		NO
LONGITUDINAL GRADE - SITE DIST. PROBLEMS:		(-) (-)		1
OBSTACLE FREE ZONE ANALYSIS:	250' WIDE x 20	0' BEYOND		/
PAVEMENT EDGE LIP HEIGHT (MIN AND MAX):	1.5" - 3"	(7)		NO
PAVEMENT MARKING TYPE:	NPI	BASIC W/ FIX	FD DIST	NO
PAVEMENT MARKING CONDITION:		POOR		N/A
17WEWENT WANTEN		1 0010		14//
RUNWAY <u>16</u> END INVENTORY				
SAFETY AREA (RSA) BEYOND RUNWAY END:	300'	OK		✓
OBJECT FREE AREA (OFA) BEYOND RUNWAY END:	300'	OK		✓
APPROACH OBSTRUCTIONS:	20:1	NONE		✓
RUNWAY END ELEVATION:			5,153.0	N/A
RUNWAY 34 END INVENTORY				
SAFETY AREA (RSA) BEYOND RUNWAY END:	300'	ОК		/
OBJECT FREE AREA (OFA) BEYOND RUNWAY END:	300'	(4)		NO
APPROACH OBSTRUCTIONS:	20:1	NONE		100
RUNWAY END ELEVATION:	20.1	INOINE	5.241.0	N/A
RUNWAT END ELEVATION.			3,241.0	IN/A
RUNWAY LIGHTING INVENTORY				
DISTANCE FROM PAVEMENT EDGE:	10'	10'		✓
MAXIMUM DISTANCE BETWEEN LIGHTS:	200'	OK		✓
TYPE:	MIRL - STAKE	MOUNTED - ADB	-ALNACO	N/A
CONDITION:		GOOD (8)		N/A
COLOR:	WHITE	WHITÈ		✓
TUDECUOLD 46				
THRESHOLD 16 DISTANCE FROM PAVEMENT EDGE:	101	40!		
	10'	10'		/
MAXIMUM DISTANCE BETWEEN LIGHTS:	10'	10		√
COLOR:	RED/GREEN	RED/GREEN		✓
THRESHOLD 34				
DISTANCE FROM PAVEMENT EDGE:	10'	10'		✓
MAXIMUM DISTANCE BETWEEN LIGHTS:	10'	10'		/
COLOR:	RED/GREEN	RED/GREEN		1
	1			

COMMENTS:

- (1) FENCE AND ROAD IN OFA EAST OF 16 END , 150' OFF CL, BUT ~12' BELOW RNWY GRADE
- (2) NON FRANGIBLE SIGN ~155' W. OF CL ON 16 END TURNAROUND IN OFA AND PRIMARY SURFACE
- (3) FENCE FROM (1) WHERE IT GOES UP&OVER TRANSVERSE ROAD, 2-3' HIGHER THAN R/W IN OFA & PRIMARY SURFACE
- (4) PILE OF MATERIAL 200' FROM 34 END ~210' W. OF CL, ~2' HIGHER THAN RNWY, IN OFA AND PRIMARY SURFACE
- (5) WIND TEE IN OFA AND PRIMARY SURFACE, APPROX 235' E. OF CL
- (6) WIND CONE ON 16 END AND BEACON VERY CLOSE TO BEING IN TRANSITIONAL SURFACE
- (7) PAVEMENT ON MOST RECENT EXTENSION OF RNWY 16 @ 1"+, REMAINING RUNWAY FLUSH
- (8) MISSING LIGHT NEAR APRON TAXIWAY ON E. SIDE OF 16/34

MONTANA STATE AVIATION SYSTEM PLAN 1995 UPDATE FIELD INSPECTION FORM

AIRPORT:	DILLON (DLN)	AIRPORT REFERENCE CODE:	B-I (SM)	
CITY:	DILLON	APPROACH TYPE:	VISUAL	
CONTACT:	CECIL JONES	DATE INVENTORIED:	12-24-95	
PHONE #:	683-6151	INSPECTED BY:	RSD	

	REQUIRED	ACTUAL	ALP	CONFORM
RUNWAY 3/21 INVENTORY				
DISTANCE TO:				
HOLD LINES FROM CENTERLINE:	125'	125'		✓
PARALLEL TAXIWAY FROM CENTERLINE:	150'	N/A		N/A
AIRCRAFT PARKING FROM CENTERLINE:	125'	200'		1
RUNWAY WIDTH:	60'	60'		/
RUNWAY LENGTH:	6,430 (1)		3,600'	<75%
RUNWAY SAFETY AREA (RSA) WIDTH:	120'	OK	,	/
RUNWAY OBJECT FREE AREA (OFA) WIDTH:	250'	OK		✓
PRIMARY / TRANSITION SURFACE PENETRATIONS:	250' W & 7:1	OK		/
LONGITUDINAL GRADE - SITE DIST. PROBLEMS:		OK		√
OBSTACLE FREE ZONE ANALYSIS:	250' WIDE x 20	0' BEYOND		/
PAVEMENT EDGE LIP HEIGHT (MIN AND MAX):	1.5" - 3"	FLUSH		NO
PAVEMENT MARKING TYPE:	BASIC	BASIC		1
PAVEMENT MARKING CONDITION:		POOR		N/A
.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,				1 471
RUNWAY 3 END INVENTORY				
SAFETY AREA (RSA) BEYOND RUNWAY END:	240'	OK		√
OBJECT FREE AREA (OFA) BEYOND RUNWAY END:	240'	(2)		NO
APPROACH OBSTRUCTIONS:	20:1	NONE		✓
RUNWAY END ELEVATION:			5,217.6	N/A
RUNWAY 21 END INVENTORY				
SAFETY AREA (RSA) BEYOND RUNWAY END:	240'	OK		/
OBJECT FREE AREA (OFA) BEYOND RUNWAY END:	240'	OK		1
APPROACH OBSTRUCTIONS:	20:1	NONE		/
RUNWAY END ELEVATION:			5.223.1	N/A
			0,220	1,471
BUNNAL COLUMN (SAITOR)				
RUNWAY LIGHTING INVENTORY				
DISTANCE FROM PAVEMENT EDGE:	10'	10'		√
MAXIMUM DISTANCE BETWEEN LIGHTS:	200'	OK		√
TYPE:	MIRL - STAKE	MOUNTED - ADB-	ALNACO	N/A
CONDITION:		GOOD (3)		N/A
COLOR:	WHITE	WHITE		√
THRESHOLD 3				
DISTANCE FROM PAVEMENT EDGE:	10'	10'		✓
MAXIMUM DISTANCE BETWEEN LIGHTS:	10'	10		/
COLOR:	RED/GREEN	RED/GREEN		1
THRESHOLD 21	101	40'		
DISTANCE FROM PAVEMENT EDGE:	10'	10'		/
MAXIMUM DISTANCE BETWEEN LIGHTS:	10'	10'		/
COLOR:	RED/GREEN	RED/GREEN		✓

COMMENTS:

(1	1) R/W LENGTH OF 4,610' FOR 75%, 6,320' FOR 95% AND 6,420' FOR 100% COVERAGE; ALP ULT OF 5,200' SHO'	WN
	(80% OF PRIMARY RUNWAY LENGTH IS 5 200' - DOES NOT COMPLY)	

⁽²⁾ APPROXIMATELY 70'-80' OF FENCELINE AND VORTAC ACCESS ROAD IN WEST CORNER OF OFA

⁽³⁾ MISSING END LIGHT ON RNWY END 3 AND ONE MISSING RUNWAY LIGHT ON SOUTH SIDE

MONTANA STATE AVIATION SYSTEM PLAN 1995 UPDATE FIELD INSPECTION FORM

AIRPORT:	DILLON (DLN)	AIRPORT REFERENCE CODE:	B-II (SM)
CITY:	DILLON	APPROACH TYPE:	VISUAL
CONTACT:	CECIL JONES	DATE INVENTORIED:	12-24-95
PHONE #:	683-6151	INSPECTED BY:	RSD

	REQUIRED	ACTUAL	ALP	CONFORM
TAXIWAY INVENTORY				
TAXIWAY WIDTH:	35'	35'		✓
TAXIWAY SAFETY AREA WIDTH:	79'	OK		✓
TAXIWAY OBJECT FREE AREA WIDTH:	131'	OK		✓
DIST. FROM CENTERLINE TO FIXED OR MOVEABLE OBJ.	65.5'	OK		✓
PAVEMENT EDGE LIP HEIGHT (MIN AND MAX):	1.5" - 3"	FLUSH		NO
PAVEMENT MARKING TYPE:		YELLOW		✓
PAVEMENT MARKING CONDITION:		FAIR (1)		N/A
TAXIWAY LIGHTING INVENTORY		(1)		
DISTANCE FROM PAVEMENT EDGE:	10'	10'		✓
MAXIMUM DISTANCE BETWEEN LIGHTS:	200'	OK		✓
TYPE:		REFLECTORS		✓
CONDITION:		GOOD		N/A
COLOR:	BLUE	BLUE		✓

MISCELLANEOUS	
TYPE OF BEACON:	60' STEEL TOWER BY ADMINISTRATION BLDG
SIZE OF BEACON:	36"
OTHER LIGHTING AIDS (VASI,PAPI,REIL):	16 & 21 ENDS: ADB ALNACO PAPI, GOOD COND, 50' OFF PVMT EDGE CONTROLERS ONLY ~4" OFF CONCRETE
WINDCONE (CONDITION & COMPLIANCE):	350' E. OF 16/34 @ MIDFIELD, LIGHTED, 25' HIGH, GOOD COND
SEGMENTED CIRCLE (CONDITION & COMPLIANCE):	METAL PANEL IN FAIR COND
WINDCONE (CONDITION & COMPLIANCE):	16 END NEAR WEST FENCE, NOT LIGHTED, ~325' W. OF CL, NEW, 15' HIGH
SEGMENTED CIRCLE (CONDITION & COMPLIANCE):	NONE
FENCING:	GOOD
SIGNS: (TYPE, CONDITION, PLACEMENT)	FOUR ADB ALNACO, GOOD COND, 15' OFF PVMT EDGE 130' FROM CL

COMMENTS:
1) TAXIWAY EXITING OFF 16/34 IS LIGHTED, ALL OTHERS REFLECTORS